

SPRING APPLIED BRAKE



TYPE 56



SG Transmission

Electromagnetic Clutch & Brake Solutions

SG Transmission, 20 Longfield Road, South Church Enterprise Park, Bishop Auckland, County Durham, UK, DL14 6XB
Tel: +44 (0)1388 770 360 Fax: +44 (0)1388 779 197 sales@sgtransmission.com www.sgtransmission.com






SECTION AA
SCALE 1:1



European standard

Unit ref	Static Torque (Nm)	OD A (mm)	Length L (mm)	Maximum Bore diameter(mm)	PCD (mm)	Power (Watts)	Voltage (V)
SB-05	5	84.0	35.0	12	72.0	20	24
SB-10	10	102.0	41.0	15	90.0	25	24
SB-20	20	127.0	47.5	24	112.0	30	24
SB-35	35	147.0	54.5	28	132.0	39	24
SB-60	60	162.0	64.0	32	145.0	47	24
SB-100	100	188.0	71.0	**	170.0	60	24
SB-170	170	215.0	83.0	**	196.0	70	24
SB-300	300	252.0	97.0	**	230.0	100	24

**Refer to factory
Maximum speed 3600 rpm
Other voltages available on request



Customised brakes

Unit ref	Static Torque (Nm)	OD A (mm)	Length L (mm)	Maximum Bore diameter (mm)	Power (Watts)	Voltage (V)
SA-35	0.15	35.0	27.0	6.0	5.0	12 or 24
SA-40	0.4	40.0	30.5	8.0	5.3	12 or 24
SA-42	0.4	42.0	32.0	8.0	5.0	12 or 24
SA-55	2.5	55.0	32.0	8.0	12.0	12 or 24
SA-60	4	60.0	32.0	12.0	15.0	12 or 24
SA-70	7	70.0	34.1	15.0	15.0	12 or 24
SA70-1	10	70.0	46.5	15.0	17.3	12 or 24
SA-77	6	77.0	39.9	20/25*	16.0	12 or 24
SA77-1	12	77.0	39.9	20/25*	20.0	12 or 24
SA-90	20	90.0	43.9	20/25*	20.0	12 or 24

*20 with key / 25 without